

SP-4B-Fixed site sampler in plastic housing, especially suited for high ambient temperatures. For automatic sample extraction according to the vacuum principle. Mains operation 230V/50Hz.

Housing Made of PE with 50 mm insulation/Styrosun/PC (GF10). Housing separated in lower part (sample compartment) and upper part (control). Each part with lockable door resp. hood. Protective hood (made of Styrosun) which can be opened for operation of the control unit and service at the dosing unit.

Thermostatic control Self-contained, automatic cooling and heating of the sample compartment to +4°C independent of the programmable controller, with protection against overheating and automatic defrost cycle, 3-point control.

Control Microprocessor control with 4 MB Flashrom, 32KB RAM (batterybuffered), 32 KB EEPROM, 3 digital inputs and 8 digital outputs, 1 configurable analogue input, battery-buffered real-time clock. Operation by means of a waterproof foil keyboard (with keys 0-9, ESC, ENT, cursor) and 4 x 20 character back lit LC-display.

Languages Multi-language, selectable

Programming Time display: Hours, minutes, seconds weekday, day, month, year

Sampling: - Time-related
- Flow-related analogue (0/4-20mA) or digital
- Event-related or in combination Option: flow-proportional

Interval: 1 min to 99 h 59min

Bottle filling: 1 min to 99 h 59 min

Programs: 6 user programs (can be edited freely)

Data memory: Logging of sample extraction data and malfunction messages. Option: storage of external data

Interface RS 232 (internal on CPU board in plug-in version, not led to the outside).
Option: Profibus/Modbus

Modem Option: GSM, AT or ISDN modem for program changes, status demand, data fetch or message transmission as SMS.

PC software Option: PC communication software

Status messages Option: Sampling, distributor, program active and collective malfunction message by means of potential-free make contacts. Can be extended to up to 8 outputs. In addition, the desired messages (configurable by means of the software) can be transmitted via modem as SMS or text file.

Dosing system

The following variants are available:

Variant 1 -VACUUM SYSTEM 350/500 ml

Variant 2 -VACUUM SYSTEM automatic Flow-proportional/VAR 350 ml

Pneumatic unit

Diaphragm pump 12 V / 4 A, vacuum 7,0 m, pressure 1 bar with motor-driven valve system for change-over from pressure/vacuum/aeration.

Average suction speed at suction hose ID 12 mm and 5 m suction height > 60 cm/sec. (according to ISO5667)



Distributor system The distributor systems can be changed easily without the need of tools.

Sample bottles

1 x 25,0 L PE
4 x 14,0 L PE
12 x 2,9 L PE
12 x 2,0 L glass
24 x 1,0 L PE
24 x 1,0 L glass

Dimensions 1.100 x 760 x 745 mm (h x w x d) – overall dimensions -

Weight Approx. 75 kg

Power supply 230 V / 50 Hz., fuse protection 10 A

Opt. coupler input Minimum voltage approx. 3,3 V

Power consumption Approx. 350 VA

Ambient temp. -20° C - + 45° C

Standards All devices meet ISO 5667 standard

Make: **MAXX**

Type: SP4 B

Manufacturer:

MAXX Mess- und Probenahmetechnik GmbH
Hechinger Straße 41, D-72414 Rangendingen
Phone +49(0)7471-98481 0, Fax +49(0)7471-98481 44
e-mail: info@maxx-gmbh.com
Internet: www.maxx-gmbh.com

Subject to technical changes. *) Patent No. DE 19726550A1, DE 19726549A1 and
VAR unit DE 10008623.3