

SERVOMEX 5200 FOOD PACK

PORTABLE BENCHTOP GAS ANALYZER

For dependable quality control and checking of gas mixtures in Modified Atmosphere Packaging (MAP)

- Non-depleting paramagnetic and infrared measurement technology ensures the unit is always ready for use
- Accurate, reliable and easy to use
- Customer pre-tested software offers ease of use, simple calibration and advanced features including data logging to assist traceability
- Innovative construction gives a robust unit with a space saving footprint
- Rechargeable battery option



SPECIFICATION

GASES MEASURED	Oxygen (O ₂) and/or Carbon Dioxide (CO ₂)	
SENSORS	OXYGEN	CARBON DIOXIDE
Technology:	Paramagnetic	Infrared
Full scale range (FSR):	0-100% O ₂	0-10%, 0-50% & 0-100% CO ₂
Minimum output range:	0-10% O ₂	0-10% FSR
Decimal places:	1	10% range: 2, others: 1
PERFORMANCE		
Accuracy general use:	±0.2% O ₂	±2% FSR
Accuracy, stable environment:	±0.1% O ₂	±1% FSR (after 20 minute warm up)
Zero drift, per week:	±0.4% O ₂	±4% FSR
Operating temperature:	+41°F to +113°F (5°C to +45°C)	+41°F to +113°F (5°C to +45°C)
Datalogging:	Up to 200 measurements stored in internal memory	
Calibration tracking:	Password protected record of time since last calibration to assist traceability	
Multilingual interface:	English, French and German languages supported as standard	
Accessories kit:	Sampling accessories for internal or external pump options	

MINIMUM SAMPLE VOLUME

	Internal pump*	Solenoid with external pump
O ₂	16ml	3.5ml
CO ₂	8ml	2ml
O ₂ and CO ₂	22ml	5ml

*These values are for optimum performance, smaller volumes may be achieved

SERVOMEX 5200 FOOD PACK

The Servomex 5200 Food Pack Analyzer has been specifically designed to meet the demanding needs of the food industry for analysing the headspace of Modified Atmosphere Packaging (MAP). It gives fast, accurate and reliable analysis of common gas mixtures used in MAP.

This compact, portable and easy to use instrument is based upon non-depleting, component specific measurement techniques (magnetodynamic paramagnetic and infrared) for long life and minimal running costs, avoiding the problems associated with electrochemical and zirconia based methods of analysis.

The 5200 Food Pack replaces the well established Servomex 574 and 1450 analyzers.

SIZE AND WEIGHT

Dimensions: W 6.0" (150mm) x D 10.5" (260mm) x H 12.0" (300mm)
Weight: 5.7lbs (2.6Kgs) to 8.6lbs (3.9Kgs) depending on configuration

APPLICATION EXAMPLES:

Modified Atmosphere Packaging (MAP) quality checks in food and pharmaceutical industries

OPTIONS:

- | | | |
|--------------------------|---------------------------|--|
| <input type="checkbox"/> | Internal Pump | With user configurable timer |
| <input type="checkbox"/> | Solenoid valve | Use external vacuum pump or syringe to draw sample |
| <input type="checkbox"/> | External vacuum pump | For smaller volume samples (must use solenoid valve version)
Choice of 230V <input type="checkbox"/> or 110V <input type="checkbox"/> |
| <input type="checkbox"/> | Analog output | One 4-20mA output per measurement
(Note RS 232 output included as standard) |
| <input type="checkbox"/> | Rechargeable batteries | Advanced Lithium ion batteries providing 8-36 hours use depending on sensor selections |
| <input type="checkbox"/> | Printer | Preformatted compact, mains power/rechargeable printer |
| <input type="checkbox"/> | 2 years spares | Recommended spares for 2 years operation, comprising replacement filters, sticky pads and syringe needles |
| <input type="checkbox"/> | QuickConnect barb fitting | Allows outlet connection to ¼" (6.3mm) ID tube |
| <input type="checkbox"/> | ½" NPT connector | Allows outlet connection to ½" NPT pipe |
| <input type="checkbox"/> | Can-piercing kit | To sample the headspace in rigid containers, such as cans. |

ADDITIONAL ACCESSORIES AVAILABLE (consult your local sales contact)

NOTE: These analyzers are not medical devices as defined by the Medical Devices Directive 93/42EEC and are not intended to be used on human beings for the diagnosis, prevention, monitoring, treatment or alleviation of disease, injury or replacement or modification of the anatomy.

SERVOMEX COMPANIES, AGENTS AND REPRESENTATIVES ARE LOCATED THROUGHOUT THE WORLD. FOR YOUR NEAREST CONTACT VISIT WWW.SERVOMEX.COM

Servomex has a policy of constant product improvement and therefore reserves the right to change specifications without notice.



Certificate No. Q05166
BS EN ISO 9001



Certificate No. EMS82701
BS EN ISO 14001



EAME (Europe, Africa and Middle East):

Servomex Group Limited, Jarvis Brook, Crowborough, East Sussex, TN6 3DU, England
Servomex GmbH, Münsterstraße 5, 59065 Hamm, Germany
Servomex S.A., 8 Rue Proudhon, B.P. 50, 93212 St Denis La Plaine Cedex, France
Servomex B.V., Stephensonstraat 20, 2723 RN Zoetermeer, Netherlands
Servomex Group Limited, SAIF Zone, Executive Suites Z1-56, PO Box 8962, Sharjah, UAE.

AMERICAS:

Servomex Company Inc., 525 Julie Rivers, Suite 185, Sugar Land, Texas 77478-2847, USA.

ASIA PACIFIC:

Servomex Asia Pacific Ltd, (Spectris Instrumentation and Systems (Shanghai) Ltd)
Building 9, Shanghai Euromate Industrial Park, No.88 Lane 2888 Hua Ning Road, Xinzhuang Industrial Park, Shanghai 201108 PR China
Servomex Asia Pacific Ltd, 7F, No.88, Sec. 6, Chung Shan N. Rd., Taipei, Taiwan
Servomex India, (Spectris Technologies Pvt.Ltd) 7th Floor, Sunil Enclave, CTS No.307, Village Gundavli, Shivaji & Perriera Hill Road Junction, Opp. Landmark Building, Off Andheri Kurla Road, Andheri (East), Mumbai 400 099, India.
Servomex Japan, (Spectris Co.Ltd) 1F KDX Kaji-cho Bldg., 3-5-2 Kandakaji-chou, Chiyoda-ku, Tokyo 101-0045, Japan

Global email: info@servomex.com

☎ (44) 1892 652181 Fax (44) 1892 662253
☎ (49) 23 81 68 82 13 Fax (49) 23 81 68 81 75
☎ (33) 1 49 46 22 50 Fax (33) 1 49 46 22 51
☎ (31) 79-346 42 42 Fax (31) 79-342 08 19
☎ (971) 6 557 0303 Fax (971) 6 557 1242

☎ (1) 281-295-5800 Fax (1) 281-295-5899

☎ (86) 21 6442 6488 Fax (86) 21 6442 6498
☎ (886) 2-2833 8848 Fax (886) 2-2833 8844

☎ (91) 22 67100359/60 Fax (91) 22 66778896
☎ (81) 3 3255 8162 Fax (81) 3 3255 8154

Website: <http://www.servomex.com>