

Hydrogen Sulfide - Sulfur Dioxide Analyzer, Model 450i


Pulsed fluorescence gas analyzer



Key Features

- ◆ Pulsed excitation and intensity stabilization
- ◆ Reflective bandpass filters
- ◆ Temperature stabilization reaction chamber
- ◆ Stable, long-life UV source
- ◆ Superior zero stability

Utilizing pulsed fluorescence technology the Model 450i H₂S and SO₂ analyzer operates on the principle that H₂S can be converted to SO₂. As the SO₂ molecules absorb ultraviolet (UV) light and become excited at one wavelength, the molecules then decay to a lower energy state emitting UV light at a different wavelength. Specifically,



The pulsing of the U.V. source lamp serves to increase the optical intensity whereby a greater U.V. energy throughput and lower detectable SO₂ concentration are realized. Reflective bandpass filters, as compared to commonly used transmission filters, are less subject to photochemical degradation

and are more selective in wavelength isolation. This results in both increased detection specificity and long term stability.

This state-of-the-art gas analyzer also offers features such as an ethernet port as well as flash memory for increased data storage. Ethernet connectivity provides efficient remote access, allowing the user to download measurement information directly from the instrument without having to be on-site.

You can easily program short cut-keys to allow you to jump directly to frequently accessed functions, menus or screens. The larger interface screen can display up to five lines of measurement information while primary screen remains visible.

Comprehensive Service Solutions

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. Thermo Fisher Scientific offers comprehensive, flexible support solutions for all phases of the product lifecycle. Through predictable, fixed-cost pricing, our services help protect the return on investment (ROI) and total cost of ownership of your Thermo Scientific air quality products.

Product Specifications

Preset Ranges	0-0.05, 0.1, 0.2, 0.5, 1, 2, 5, and 10 ppm 0-0.2, 0.5, 1, 2, 5, 10, 20, and 25 mg/m ³				
Extended Ranges	0-0.5, 1, 2, 5, 10, 20, 50 and 100 ppm 0-2, 5, 10, 20, 50, 100, 200, and 250 mg/m ³				
Custom Ranges	0-0.05 to 100 ppm 0-0.2 to 250 mg/m ³				
Zero Noise	1.0 ppb	Manual	H ₂ S or CS	3.0 ppb	Auto (10 second averaging time)
	0.5 ppb			1.5 ppb	(60 second averaging time)
	0.25 ppb			0.75 ppb	(300 second averaging time)
Lower Detectable Limit	2.0 ppb	Manual	H ₂ S or CS	6.0 ppb	Auto (10 second averaging time)
	1.0 ppb			3.0 ppb	(60 second averaging time)
	0.5 ppb			1.5 ppb	(300 second averaging time)
Zero Drift (24 hour)	Less than 1 ppb				
Span Drift (24 hour)	+/-1% Full Scale				
Response Time	80 seconds (10 second average time) 110 seconds (60 second average time) 320 seconds (300 second average time)				
Precision	1% of reading or 1 ppb (whichever is greater)				
Linearity	+/-1% full scale				
Sample Flow Rate	1.0 liter/min.				
Converter Efficiency	> 80% H ₂ S to SO ₂ . Note: Various other Sulfur compounds can be converted at varying %				
Operating Temperature	20°C - 30°C				
Power Requirements	100 vac, 115 vac, 220-240 vac +/-10% @ 300W				
Size and Weight	16.75"(W) x 8.62"(H) x 23"(D), 48 lbs. (21.8 kg)				
Outputs	Selectable Voltage, RS232/RS485, TCP/IP, 10 Status Relays, and Power Fail Indication (standard). 0-20 or 4-20 mA Isolated Current Outout (optional)				
Inputs	16 Digital Inputs (standard), 8 0-10vdc Analog Inputs (optional)				
Available Options	Teflon particulate filter, Rack mounts, Rear extenders				

Ordering Information

Model 450i H₂S/SO₂ Analyzer

Choose from the following configurations/options to customize your own Model 450i

Voltage options:

A = 115 Vac 50/60 Hz
B = 220 Vac 50/60 Hz
J = 100 Vac 50/60 Hz

Internal zero /span:

N = No zero / span assembly
Z = Internal zero / span assembly
P = Internal permeation span source with zero/span assembly

Sample Handling:

S = Standard
E = External Converter Setup (no converter supplied)
H = Selective SO₂ Scrubber (Continuous H₂S Analysis only)

Optional I/O:

A = No optional I/O (standard)
C = 0-20, 4-20mA current output - 6 channels, 0-10v analog input - 8 channels

Mounting hardware:

A = Bench mounting (standard)
B = Ears & handles, EIA
C = Ears & handles, retrofit

Your Order Code: 450i - _ _ _ _ _



This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. © 2008 Thermo Fisher Scientific. All rights reserved Thermo Fisher Scientific, Inc.

Environmental Instruments

Air Quality Instruments

27 Forge Parkway
Franklin, MA 02038

+1 (866) 282-0430
+1 (508) 520-1460 (fax)

Takkebijsters 1
Breda, BL 4817
The Netherlands

+33 (0) 76 5879888
+33 (0) 76 5816520 (fax)

www.thermo.com/air

Lit_450iAQI_0708

Thermo
SCIENTIFIC