

## Model 146i Multi-gas Calibrator

Mass flow calibrator with enhanced communication capabilities for ambient air monitoring.



### Key Features

- ◆ Ethernet connectivity for efficient remote access
- ◆ Enhanced user interface with one button programming and large display screen
- ◆ Flash memory for increased data storage and user downloadable software
- ◆ Enhanced electronics design optimizes product commonality
- ◆ Improved layout for easier accessibility to components
- ◆ Gas Phase Titration for Generation of O<sub>3</sub> and NO<sub>2</sub>

### A change is in the air

The Thermo Electron Model 146i Dynamic Gas Calibrator supplies precise levels of ozone, carbon monoxide, non-methane hydrocarbons, sulfur dioxide, nitric oxide and nitrogen dioxide or other gases that a user may require. The gas levels are used to calibrate instruments that perform zero, precision and level 1 span checks, audits and multipoint measurements. The design of the Model 146i meets or exceeds all published U.S. Environmental Protection Agency requirements for multipoint calibration, audit, Level 1 and 2 span and precision checks. Options include Gas Phase Titration, UV Photometer, and Permeation Oven

The Model 146i's mass flow controller, ozone generator, permeation tube oven, power supply, and solenoid valves are integrated into a single microprocessor controlled unit. This permits easy to use, menu driven software and a consistent set of operation screens for all calibration procedures. Additionally, the microprocessor can make many of the necessary calculations, thereby freeing the operator from having to make the calculations in the field or laboratory. If desired, the Model 146i can be operated remotely by a data logger or to perform multipoint calibrations.

## Comprehensive Service Solutions

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. Thermo Scientific offers comprehensive, flexible support solutions for all phases of the product lifecycle. Through predictable, fixed-cost pricing, Thermo Scientific services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

### Product Specifications

#### Dilution System

Flow Measurement Accuracy	+/- 2% setpoint or +/- 1% FS, whichever is less from 20 to 100% FS
Repeatability of flow control	+/- 0.2% FS (Porter flow controller spec - better than 146C)
Linearity of mass flow measurements	+/- 0.5% FS
Flow range of dilution air	0-10 SLPM
optional ranges	0-5/0-20 SLPM
Flow range of cylinder gases	0-100SCCM
optional ranges	0-50/0-200 SCCM
Zero Air requirements	10 SLPM @ 30 PSI
optional ranges	20 SLPM @ 30 PSI
Calibration gas input ports	3, optional 6
Diluent gas input ports	1
Response time	<60 sec. To 99% (146C spec)

#### Ozone Generator Option

Maximum output	1 ppm @ 6 SLPM
Minimum output	10 ppb @ 6 SLPM

#### Photometer System

Full Scale Range	100 ppb to 5 ppm user selectable
Linearity	1% of Full Scale
Precision	1 ppb
Response Time	180 Seconds to 95% of Target
Minimum Detectable Limit	3 ppb

#### Physical Specifications

Test channel analog	6 @ +/- 100 mv, 1,5,10 volts (user selectable)
Digital control outputs	10 Relay and 8 24vdc Solenoid
Digital control inputs	16
Temperature range	0-40 deg.C
Weight	51 lbs (58 lbs for 220-240VAC)
Dimensions	16.75" W x 8.62" H x 23" D
Power	100VAC 50/60Hz, 115VAC 50/60Hz, 220-240VAC 50/60Hz, 275 watts (with all options)

### Ordering Information

#### Model 146i Calibrator

Choose from the following configurations/options to customize your own Model 146i

#### Voltage options:

A = 120 Vac 50/60 Hz (standard)  
 B = 220 Vac 50/60 Hz  
 J = 100 Vac 50/60 Hz

#### Calibration Sources

N = No Optional Calibration Sources (standard)  
 P = Internal Permeation Span Source  
 T = Gas Phase Titration  
 B = Gas Phase Titration with Photometer  
 C = Internal Permeation Span Source with Gas Phase Titration  
 D = Internal Permeation Span Source with Gas Phase Titration and Photometer

#### Span Ports

3 = Three Span Inputs (standard)  
 6 = Six Span Inputs

#### Other options:

- Rack mounts
- Rear extender
- Terminal Block Kit & Cable 37 pin
- Cable, DB25M to open end, 6' LG.

#### Span Gas Mass Flow Controller

A = 50 SCCM  
 B = 100 SCCM (standard)  
 C = 200 SCCM

#### Zero Gas Mass Flow Controller

D = 5 SLPM  
 E = 10 SLPM (standard)  
 F = 20 SLPM

#### Optional I/O:

A = None (standard)  
 C = I/O expansion board  
 (4-20mA outputs - 6 channels, 0-10v inputs - 8 channels)

#### Mounting Hardware:

A = Bench mounting (standard)  
 B = Ears & handles, EIA  
 C = Ears & handles, Retrofit

Your Order Code: 146i - \_ \_ \_ \_ \_

- Cable, DB37M to open end, 6' LG.
- Cable, DB37F to open end, 6' LG.
- Terminal Block Kit & Cable 25 pin
- Cable, RS232 Null Modem

This specification sheet is for informational purposes only and is subject to change without notice. Thermo makes no warranties, expressed or implied, in this product summary.  
 © 2006 Thermo Fisher Scientific. All rights reserved.

